

Appl. No. 10/604,854
Amdt. dated March 24, 2006
Reply to Office action of January 13, 2006

Amendments to the Claims:

Listing of Claims:

Claims 1-11 (cancelled)

5

12 (previously presented): A backlight unit for changing lamps therein conveniently, the backlight unit comprising:

at least an optical sheet and a diffusion plate fixed to a backside of a display panel, the optical sheet and the diffusion plate forming an upper module with the display panel;

10

a top frame for accommodating and fixing the upper module;

a bottom frame positioned below the upper module and fixed to the top frame;

a plurality of lamps positioned within the bottom frame;

a plurality of buffer sheets positioned on portions of surfaces contacting with the lamps; and

15

a plurality of fixing elements positioned on the top frame and the bottom frame for detachable connection of the bottom frame to the top frame;

wherein the backlight unit is capable of changing the lamps within the bottom frame after removal of the upper module above the bottom frame.

20

13 (previously presented): The backlight unit of claim 12 wherein the optical sheet comprises at least a diffuser sheet and a prism sheet.

14 (previously presented): The backlight unit of claim 12 wherein the bottom frame comprises a reflecting sheet surrounding the lamps.

25

15 (previously presented): The backlight unit of claim 12 wherein the top frame comprises a plurality of fixing elements for fixing the optical sheet and the diffusion plate

Appl. No. 10/604,854
Amdt. dated March 24, 2006
Reply to Office action of January 13, 2006

to the backside of the display panel.

16 (previously presented): The backlight unit of claim 12 wherein the fixing elements comprise screws.

5

17 (previously presented): The backlight unit of claim 12 wherein the lamps comprise cold cathode fluorescent lamps.

18 (previously presented): The backlight unit of claim 12 wherein the lamps comprise
10 external electrode fluorescent lamps.

19 (previously presented): The backlight unit of claim 18 wherein a conductive clip is positioned at an external electrode of the external electrode fluorescent lamps to simplify procedures of changing the lamps.

15

20 (previously presented): A backlight unit for changing lamps therein conveniently, the backlight unit comprising:

at least an optical sheet and a diffusion plate fixed to a backside of a display panel, the optical sheet and the diffusion plate forming an upper module with the display panel;

20 a top frame for accommodating and fixing the upper module, wherein the top frame comprises a plurality of first fixing elements for fixing the optical sheet and the diffusion plate to the backside of the display panel;

a bottom frame positioned below the upper module and fixed to the top frame;

a plurality of lamps positioned within the bottom frame; and

25 a plurality of second fixing elements positioned on the top frame and the bottom frame for detachable connection of the bottom frame to the top frame;

wherein the backlight unit is capable of changing the lamps within the bottom frame after removal of the upper module above the bottom frame.

Appl. No. 10/604,854
Amdt. dated March 24, 2006
Reply to Office action of January 13, 2006

21 (previously presented): A backlight unit for changing lamps therein conveniently, the backlight unit comprising:

- at least an optical sheet and a diffusion plate fixed to a backside of a display panel,
- 5 the optical sheet and the diffusion plate forming an upper module with the display panel;
- a top frame for accommodating and fixing the upper module;
- a bottom frame positioned below the upper module and fixed to the top frame;
- a plurality of lamps positioned within the bottom frame; and
- a plurality of screws positioned on the top frame and the bottom frame for
- 10 detachable connection of the bottom frame to the top frame;
- wherein the backlight unit is capable of changing the lamps within the bottom frame after removal of the upper module above the bottom frame.

22 (previously presented): A backlight unit for changing lamps therein conveniently, the backlight unit comprising:

- at least an optical sheet and a diffusion plate fixed to a backside of a display panel,
- the optical sheet and the diffusion plate forming an upper module with the display panel;
- a top frame for accommodating and fixing the upper module;
- a bottom frame positioned below the upper module and fixed to the top frame;
- 20 a plurality of external electrode fluorescent lamps positioned within the bottom frame, wherein a conductive clip is positioned at an external electrode of the external electrode fluorescent lamps to simplify procedures of changing the lamps; and
- a plurality of fixing elements positioned on the top frame and the bottom frame for detachable connection of the bottom frame to the top frame;
- 25 wherein the backlight unit is capable of changing the lamps within the bottom frame after removal of the upper module above the bottom frame.

23 (new): The backlight unit of claim 20 wherein the optical sheet comprises at least a

Appl. No. 10/604,854
Amdt. dated March 24, 2006
Reply to Office action of January 13, 2006

diffuser sheet and a prism sheet.

24 (new): The backlight unit of claim 21 wherein the optical sheet comprises at least a diffuser sheet and a prism sheet.

5

25 (new): The backlight unit of claim 22 wherein the optical sheet comprises at least a diffuser sheet and a prism sheet.

10